

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 610 Renia - Edelkitt - Leather cement

Revision date: 04.01.2018

Product code: 610.000

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

610 Renia - Edelkitt - Leather cement

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives, sealants  
Roller application or brushing of adhesive and other coating.  
Reserved for industrial and professional use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	Renia Gesellschaft mbH. Chemische Fabrik	
	D	
Street:	Ostmerheimer Straße 516	
Place:	D-51109 Köln (Cologne)	
Post-office box:	910659	
	D-51076 Köln (Cologne)	
Telephone:	+49-221-630799-0	Telefax: +49-221-630799-50
e-mail:	info@renia.com	
Contact person:	Heinz Buchholz Dipl.Chem	Telephone: 16
e-mail:	labor@renia.com	
Internet:	www.renia.com	
Responsible Department:	Labor 07:30 - 16:00 Uhr	

### 1.4. Emergency telephone number:

+49-221-630799-0

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:  
Flammable liquid: Flam. Liq. 2  
Serious eye damage/eye irritation: Eye Irrit. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Hazard Statements:  
Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Classification according to Regulation (EC) No 1272/2008 [CLP]

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

acetone  
methyl acetate  
propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

#### Pictograms:



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 2 of 12

**Hazard statements**

- H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P235 Keep cool.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P370+P378 In case of fire: Use ... to extinguish.  
P501 Dispose of contents/container to ....

**Special labelling of certain mixtures**

- EUH066 Repeated exposure may cause skin dryness or cracking.

**Additional advice on labelling**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

adhesive based on nitrocellulose (nitrogenousity < 12,6 %) and synthetic resins in a mixture of organic solvents.

**Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-64-1	acetone			40-50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
79-20-9	methyl acetate			30-40 %
	201-185-2	607-021-00-X	01-2119459211-47	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			1-5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 3 of 12

necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

**After contact with skin**

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. Grease skin after contact

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Dizziness. Nausea.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam. Extinguishing powder, ABC powder. Atomized water. Dry sand.

**Unsuitable extinguishing media**

High power water jet. High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Cover drains.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 4 of 12

**Advice on safe handling**

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advice on protection against fire and explosion**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours / aerosols must be extracted by suction immediately at point of origin. Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.  
Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

**Advice on storage compatibility**

Do not store together with: Oxidising agent, Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Floors should be impervious, resistant to liquids and easy to clean.  
Store small packages in a suitable, robust cabinet.

**7.3. Specific end use(s)**

Adhesives, sealants  
Roller application or brushing of adhesive and other coating.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
67-64-1	acetone			
	Worker DNEL, acute	inhalation	systemic	2420 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	systemic	1210 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	200 mg/m <sup>3</sup>
	Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 610 Renia - Edelkitt - Leather cement

Revision date: 04.01.2018

Product code: 610.000

Page 5 of 12

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
67-64-1	acetone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Soil		29,5 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Before starting work, apply solvent-resistant skincare preparations.

##### Eye/face protection

Tightly sealed safety glasses.

##### Hand protection

Test suitability of gloves before use.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,5 mm

Breakthrough time (maximum wearing time) :  $\geq 1$  h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Wear anti-static footwear and clothing

##### Respiratory protection

Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387) Use the following filter types for cleaning waste gases: A-P2

##### Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless, clear
Odour:	ester

#### Test method

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 6 of 12

pH-Value:	not applicable
<b>Changes in the physical state</b>	
Melting point:	-4 - +5 °C
Initial boiling point and boiling range:	56 °C DIN 53 171
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	< -20 °C DIN 51 755
Sustaining combustion:	No data available

**Flammability**

Solid:	not applicable
Gas:	not applicable

**Explosive properties**

Vapours can form explosive mixtures with air.

Lower explosion limits:	2,5 vol. %
Upper explosion limits:	16 vol. %
Ignition temperature:	455 °C DIN 51 794

**Auto-ignition temperature**

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: (at 20 °C)	246 hPa DIN EN 12
Vapour pressure: (at 50 °C)	814 hPa
Density (at 20 °C):	0,86 g/cm <sup>3</sup> DIN 51 757
Bulk density:	not applicable
Water solubility:	not determined

**Solubility in other solvents**

not determined

Partition coefficient:	not determined
Viscosity / dynamic: (at 20 °C)	900 mPa·s
Viscosity / kinematic:	not determined
Flow time:	< 300 (3 mm)
Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	78,20 %

**9.2. Other information**

Solid content:	21,80 %
----------------	---------

**SECTION 10: Stability and reactivity**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 7 of 12

**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

**10.3. Possibility of hazardous reactions**

Gas/vapour, highly flammable. Vapours can form explosive mixtures with air.

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Not to be distilled, danger of explosion.

**10.5. Incompatible materials**

Acid, concentrated. , Oxidizing agents, strong.

**10.6. Hazardous decomposition products**

In case of fire may be liberated: toxic brown nitrous vapours

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone				
	oral	LD50 mg/kg	5800	Ratte	RTECS
	dermal	LD50 mg/kg	20000	Kaninchen	IUCLID
	inhalative (4 h) vapour	LC50	76 mg/l	Ratte	
79-20-9	methyl acetate				
	oral	LD50 mg/kg	5000	Rat	
	dermal	LD50 mg/kg	2000	Rat	
	inhalative (4 h) vapour	LC50	48 mg/l	Rat	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	4570	Rat	
	dermal	LD50 mg/kg	13450	Rabbit	
	inhalative (4 h) vapour	LC50	30 mg/l	Rat	

**Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Frequently or prolonged contact with skin may cause dermal irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 8 of 12

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

**STOT-single exposure**

May cause drowsiness or dizziness. (acetone; methyl acetate)

There are no data available on the preparation/mixture itself.

**STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the preparation/mixture itself.

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

Product is easily volatile. Product is slightly soluble in test vehicle. An aqueous dispersion has been tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
79-20-9	methyl acetate					
	Acute fish toxicity	LC50	350 mg/l	96 h	Brachadanio rerio	
	Acute algae toxicity	ErC50	120 mg/l	72 h	Pseudokirchneriella subcarpitata	
	Acute crustacea toxicity	EC50 mg/l	1026	48 h	Daphnia magna	24 h
	Acute bacteria toxicity	(1830 mg/l)			Pseudomonas putida 16 h	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Scenedesmus subspicatus	

**12.2. Persistence and degradability**

Product is biodegradable with difficulty.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone			
	OECD 301 A-F	60 BSB/CSB	28	

**12.3. Bioaccumulative potential**

There are no data available on the preparation/mixture itself.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 9 of 12

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,24
79-20-9	methyl acetate	0,18
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16

**12.4. Mobility in soil**

There are no data available on the preparation/mixture itself.

**12.5. Results of PBT and vPvB assessment**

There are no data available on the preparation/mixture itself.

**12.6. Other adverse effects**

There are no data available on the preparation/mixture itself.

**Further information**

The statement is derived from the properties of the components.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

**Waste disposal number of waste from residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**Waste disposal number of used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Dispose according to legislation. Completely emptied packages can be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 10 of 12

Classification code: F1  
Special Provisions: 640H  
Limited quantity: LQ7  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 33  
Tunnel restriction code: D/E

**Other applicable information (land transport)**

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 640H  
Limited quantity: 5 L  
Excepted quantity: E1

**Other applicable information (inland waterways transport)**

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

**Marine transport (IMDG)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: No  
Special Provisions: 223, 955  
Limited quantity: 5 Liter  
Excepted quantity: E1  
EmS: F-E, S-D

**Other applicable information (marine transport)**

Additional information on classification : 2.3.2.3 IMDG-Code

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 610 Renia - Edelkitt - Leather cement

Revision date: 04.01.2018

Product code: 610.000

Page 11 of 12



Special Provisions:	A3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

2010/75/EU (VOC):	100 % (860 g/l)
2004/42/EC (VOC):	100 % (860 g/l)

##### National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**610 Renia - Edelkitt - Leather cement**

Revision date: 04.01.2018

Product code: 610.000

Page 12 of 12

H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*