

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

131.000 Renia - Klebfest tf Contact Adhesive tf

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants
Roller application or brushing of adhesive and other coating.
Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

| | | |
|-------------------------|--|----------------------------|
| Company name: | Renia Gesellschaft mbH. Chemische Fabrik | |
| | D | |
| Street: | Ostmerheimer Straße 516 | |
| Place: | D-51109 Köln (Cologne) | |
| Post-office box: | 910659 | |
| | D-51076 Köln (Cologne) | |
| Telephone: | +49-221-630799-0 | Telefax: +49-221-630799-50 |
| e-mail: | info@renia.com | |
| Contact person: | Heinz Buchholz Dipl.Chem | Telephone: 16 |
| e-mail: | labor@renia.com | |
| Internet: | www.renia.com | |
| Responsible Department: | Labor 07:30 - 16:00 Uhr | |

1.4. Emergency telephone number:

+49-221-630799-0

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Flammable liquid: Flam. Liq. 2
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.2. Label elements**Regulation (EC) No. 1272/2008**

Hazard components for labelling
ethyl acetate

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 2 of 13

Pictograms:

Hazard statements

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|-----------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P235 | Keep cool. |
| P370+P378 | In case of fire: Use ... to extinguish. |
| P501 | Dispose of contents/container to waste management. |

Special labelling of certain mixtures

| | |
|--------|--|
| EUH208 | Contains Rosin, colophony. May produce an allergic reaction. |
|--------|--|

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

polychloroprene adhesive with modified synthetic resins and stabilizers in a mixture of organic solvents

Hazardous components

| CAS No | Chemical name | EC No | Index No | REACH No | Quantity |
|------------|---|---|--------------|------------------|-------------|
| | | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | |
| 141-78-6 | ethyl acetate | | | | 35 - < 45 % |
| | | 205-500-4 | 607-022-00-5 | 01-2119475103-46 | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066 | | | | |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha | | | | 35 - < 45 % |
| | | 265-151-9 | 649-328-00-1 | 01-2119475133-43 | |
| | Flam. Liq. 2, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H304 H411 | | | | |
| 8050-09-7 | Rosin, colophony | | | | 0.1 - < 1 % |
| | | 232-475-7 | 650-015-00-7 | 01-2119480418-32 | |
| | Skin Sens. 1; H317 | | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 3 of 13

General information

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. Grease skin after contact

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), alcohol resistant foam. Extinguishing powder, ABC powder. Atomized water. Dry sand.

Unsuitable extinguishing media

High power water jet. High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

5.3. Advice for firefighters

Special exposure hazards arising from the substance itself, combustion products, resulting gases: In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 4 of 13

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours / aerosols must be extracted by suction immediately at point of origin. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent, Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean.

Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

Adhesives, sealants Roller application or brushing of adhesive and other coating.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|---------------|-----|-------------------|-----------|---------------|--------|
| 141-78-6 | Ethyl acetate | 200 | - | | TWA (8 h) | WEL |
| | | 400 | - | | STEL (15 min) | WEL |

Safety Data Sheet

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest ff Contact Adhesive ff

Revision date: 04.01.2018

Product code: 131.000

Page 5 of 13

DNEL/DMEL values

| CAS No | Substance | | |
|--------------------------|---|----------|------------------------|
| DNEL type | Exposure route | Effect | Value |
| 141-78-6 | ethyl acetate | | |
| Worker DNEL, long-term | inhalation | systemic | 1468 mg/m ³ |
| Worker DNEL, acute | inhalation | local | 1468 mg/m ³ |
| Worker DNEL, long-term | dermal | systemic | 63 mg/kg bw/day |
| Worker DNEL, long-term | inhalation | local | 734 mg/m ³ |
| Consumer DNEL, acute | inhalation | systemic | 734 mg/m ³ |
| Consumer DNEL, long-term | inhalation | local | 734 mg/m ³ |
| Consumer DNEL, long-term | dermal | systemic | 37 mg/kg bw/day |
| Consumer DNEL, long-term | inhalation | systemic | 367 mg/m ³ |
| Consumer DNEL, long-term | oral | systemic | 4,5 mg/kg bw/day |
| Consumer DNEL, acute | inhalation | local | 367 mg/m ³ |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha | | |
| Worker DNEL, long-term | dermal | systemic | 13964 mg/kg bw/day |
| Worker DNEL, long-term | inhalation | systemic | 5306 mg/m ³ |
| Consumer DNEL, long-term | dermal | systemic | 1377 mg/kg bw/day |
| Consumer DNEL, long-term | inhalation | local | 1137 mg/m ³ |
| Consumer DNEL, long-term | oral | systemic | 1601 mg/kg bw/day |

PNEC values

| CAS No | Substance | |
|---------------------------|---------------|--|
| Environmental compartment | Value | |
| 141-78-6 | ethyl acetate | |
| Freshwater | 0,26 mg/l | |
| Marine water | 0,026 mg/l | |
| Freshwater sediment | 0,34 mg/kg | |
| Marine sediment | 0,034 mg/kg | |
| Soil | 0,22 mg/kg | |

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Before starting work, apply solvent-resistant skincare preparations.

Eye/face protection

Tightly sealed safety glasses.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 6 of 13

Hand protection

Test suitability of gloves before use.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,5 mm

Breakthrough time (maximum wearing time) : >= 1 h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Respiratory protection

Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387) Use the following filter types for cleaning waste gases: A-P2

Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|-----------------|--------------|
| Physical state: | liquid |
| Colour: | light yellow |
| Odour: | ester |

| | | |
|-----------|----------------|--------------------|
| pH-Value: | not applicable | Test method |
|-----------|----------------|--------------------|

Changes in the physical state

| | |
|--|-------------------|
| Melting point: | not determined |
| Initial boiling point and boiling range: | 65 °C DIN 53 171 |
| Sublimation point: | not determined |
| Softening point: | not determined |
| Pour point: | not determined |
| Flash point: | -18 °C DIN 51 755 |
| Sustaining combustion: | No data available |

Flammability

| | |
|--------|----------------|
| Solid: | not applicable |
| Gas: | not applicable |

Explosive properties

Vapours can form explosive mixtures with air.

| | |
|-------------------------|-------------------|
| Lower explosion limits: | 1 vol. % |
| Upper explosion limits: | 11,5 vol. % |
| Ignition temperature: | 200 °C DIN 51 794 |

Auto-ignition temperature

| | |
|--------|----------------|
| Solid: | not applicable |
| Gas: | not applicable |

| | |
|----------------------------|----------------|
| Decomposition temperature: | not determined |
|----------------------------|----------------|

Oxidizing properties

Not oxidising.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 7 of 13

| | | |
|--------------------------------|---|------------|
| Vapour pressure: (at 20 °C) | 175 hPa | DIN EN 12 |
| Vapour pressure: | 950 hPa | |
| Density (at 20 °C): | 0,84 g/cm ³ | DIN 51 757 |
| Bulk density: | not applicable | |
| Water solubility: | The study does not need to be conducted because the substance is known to be insoluble in water | |

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic:
(at 20 °C) 1200-3000 mPa·s DIN 51550Flow time:
(at 20 °C) > 300 (3 mm)

Vapour density: not determined

Evaporation rate: not determined

Solvent separation test: < 0,1 %

Solvent content: 79,50 %

9.2. Other information

Solid content: 20,50 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.2. Chemical stability

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.3. Possibility of hazardous reactions

Gas/vapour, highly flammable. Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Decomposition takes place from temperatures above: > 150 °C

10.5. Incompatible materials

Acid, concentrated. , Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 8 of 13

| CAS No | Chemical name | | | | |
|------------|---|---------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 141-78-6 | ethyl acetate | | | | |
| | oral | LD50 mg/kg | 5600 | Rat | |
| | dermal | LD50 mg/kg | 18000 | Rabbit | |
| | inhalative (4 h) vapour | LC50 | 58 mg/l | Rat | |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha | | | | |
| | oral | LD50 mg/kg | 5000 | Rat | |
| | dermal | LD50 mg/kg | 3160 | Rabbit | |
| | inhalative (4 h) vapour | LC50 | 25 mg/l | Rat | |
| 8050-09-7 | Rosin, colophony | | | | |
| | oral | LD50 mg/kg | >2000 | Rat | |
| | dermal | LD50 mg/kg | >2000 | Rabbit | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

May cause sensitization by inhalation and skin contact. Contains: Kolophonium

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Inhalation causes narcotic effects/intoxication.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Longterm fish toxicity. Product is easily volatile. Product is slightly soluble in test vehicle. An aqueous dispersion has been tested.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 9 of 13

| CAS No | Chemical name | | | | | |
|------------|---|-----------------|-----------|-------------------------|--------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 141-78-6 | ethyl acetate | | | | | |
| | Acute fish toxicity | LC50 230 mg/l | 96 h | Pimephales promelas | | |
| | Acute algae toxicity | ErC50 3300 mg/l | 72 h | Scenedesmus subspicatus | | |
| | Acute crustacea toxicity | EC50 717 mg/l | 48 h | Daphnia magna | | |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha | | | | | |
| | Acute fish toxicity | LC50 10 mg/l | 96 h | Fisch | | |
| | Acute algae toxicity | ErC50 10 mg/l | 72 h | Alge | | |
| | Acute crustacea toxicity | EC50 10 mg/l | 48 h | Daphnie | | |

12.2. Persistence and degradability

Product is biodegradable with difficulty.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|---|---------|
| 141-78-6 | ethyl acetate | 0,6 |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha | 4-5 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|----------|---------------|-----|---------|--------|
| 141-78-6 | ethyl acetate | 30 | | |

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 10 of 13

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose according to legislation. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives Hazardous Material: Naphta
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 640H
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives Hazardous Material: Naphta
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 640H
Limited quantity: 5 L
Excepted quantity: E1

Other applicable information (inland waterways transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

Marine transport (IMDG)

14.1. UN number: UN 1133

Safety Data Sheet

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 11 of 13

14.2. UN proper shipping name: Adhesives Hazardous Material: Naphta
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: No
Special Provisions: 223, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Other applicable information (marine transport)

Category: A

Additional information on classification : 2.3.2.2 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives Hazardous Material: Naphta
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**14.6. Special precautions for user**

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 12 of 13

2010/75/EU (VOC): 100 % (840 g/l)

2004/42/EC (VOC): 100 % (840 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data |
| Skin Irrit. 2; H315 | Calculation method |
| Eye Irrit. 2; H319 | Calculation method |
| STOT SE 3; H336 | Calculation method |
| Aquatic Chronic 2; H411 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|--------|--|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH208 | Contains Rosin, colophony. May produce an allergic reaction. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

131.000 Renia - Klebfest tf Contact Adhesive tf

Revision date: 04.01.2018

Product code: 131.000

Page 13 of 13

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)